

LUTUM® PRO

2020

clay printer

A **Professional version of the LUTUM®** is now available. It is equipped with a Stainless Steel worktop, an easy access interior for custom adjustments, heavy duty drivers and motor for the lateral Y-axis movement and upgraded Firmware.

This printer is intended for a professional or laboratory environment. There are more adjustable system options and a Stainless Steel worktop provides a durabe surface for extended use.

In DUAL mode it has a built in option to have both extruders run at the same time providing higher clay output or combining different materials in one extrusion.



LUTUM® PRO SPECIFICS

- HIGH PRECISION STAINLESS STEEL AUGER SCREW & EXTRUDER
- ROBUST METAL & P.E.T. CARTRIDGE CLAY DELIVERY SYSTEM
- PRE-INSTALLED SECOND AIR VALVE FOR OPTIONAL SECOND EXTRUDER
- ROBUST MECHANICS WITH ALL MOVING PARTS PROTECTED AND INCLUDING AN EMERGENCY STOP BUTTON, AIR SAFETY AND CUT-OUT VALVE
- ALL METAL PARTS ARE CUSTOM CNC MILLED, FULLY ANNODIZED AND POWDER COATED FOR EASY CLEANING
- RUNS ON AN 8BIT, 24v SYSTEM, AND HAS A CONVENIENT EXTERNAL CONTROL BOX FOR MANUAL INTERVENTION
- CAN PRINT A VARIETY OF GROGGED CLAYS UP TO 25% 0.2MM
- HAS A BUILD ENVELOPE SIZE 43X45X50 XYZ AND FULL STAINLESS STEEL WORK AREA
- FASTER PRINTING USING ADJUSTABLE ACCELERATION WITH HEAVY DUTY Y-AXIS DRIVER AND MOTOR

TECHNICAL SPECIFICATIONS current version 4.5

Technology: LDM, 8 bit electronics, 24v Extruders: 18/10 Stainless Steel Extruder

Printing volume: 430x450x500mm LWH Standard: nozzle diameter 3mm

Nozzle diameter: variable In package: 0.6mm, 1.2mm, 1.6mm, 5mm, 7mm

Layer resolution: min 0.5mm - max 4mm Operating systems: Arduino

Max speed: 150mm / s with accelerated velocity printing Slicing: SLic3r (recommended) - Simplify 3d - Cura

Materials: earthenware, stoneware, refractory, clays etc. File type: .gcode

Tolerance: print bed deviation 1 mm over max distance Interface: SD card - LCD screen - USB

First layer: 0.3mm / 100mm Physical dimensions: 75x75x105 cm

Subsequent layers: 0.1mm / 400mm Printer weight: 85kg

Extrusion output: depending on clay, needs manual intervention Air compressor: Not included





LUTUM® PRO

2020

clay printer



- → standard nozzle pack
- → control box + SD card
- → cartridge set S (700cc)
- → cartridge set L (1400cc)

- → 1 year / 1000h limited warrenty
- → metal cartridge sleeve S
- ightarrow 2 extra PET sleeve sets S
- ightarrow spare seals for Auger and Motor
- → USB cable, power cable
- → plaster printbed
- → all necessary tools
- → instruction manual







